



## Spartan Chemical Company, Inc.

### Material Safety Data Sheet

#### SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

Product Division:

**MILLENNIA BRIGHT DURA GLOSS LAMINATE****Janitorial**

Product Number: 4060

**Spartan Chemical Company, Inc.**Product/Technical  
Information: **1-(800)-537-8990****1110 Spartan Drive**Medical Emergency: **1-(888)-314-6171 (24 hours)****Maumee OH 43537**Chemical Leak/Spill  
Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description:		Buffing, polishing compounds, liquid, n.o.s.	
<b>NFPA Ratings:</b>		<b>HMIS Ratings:</b>	
<b>Health:</b>	1- Slight	<b>Health:</b>	1- Slight
<b>Fire:</b>	0 - Minimal	<b>Fire:</b>	0 - Minimal
<b>Reactivity:</b>	0 - Minimal	<b>Reactivity:</b>	0 - Minimal
		<b>Pers. Prot. Equip.:</b>	See Section VIII

#### SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	% W	CAS Registry No.	Table Z- 1 - A			NTP, IARC or OSHA Carcinogen
			TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	CEILING mg/m <sup>3</sup>	
Acrylic polymer	NA	25987-66-0	Not Established	Not Established	Not Established	No
*Diethylene glycol monoethyl ether	4.4	111-90-0	137.2 (UCC)	Not Established	Not Established	No
*Dibutyl phthalate	1.2	84-74-2	5	Not Established	Not Established	No
Tributoxyethyl phosphate	NA	78-51-3	Not Established	Not Established	Not Established	No
Ethylene copolymer	NA	67892-91-5	Not Established	Not Established	Not Established	No

Comment: \*This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

▼ **SECTION III: PHYSICAL DATA**

Boiling Point:	210-215 °F	Vapor Pressure:	Undetermined
Vapor Density (AIR = 1):	Undetermined	Solubility in Water:	Complete
pH:	8.5- 9.0	Specific Gravity (H <sub>2</sub> O=1):	1.025
Evaporation Rate (but.ace.=1):	<1	Percent Solid by Weight:	16-18
Physical State:	Liquid		
Appearance & Odor:	Translucent emulsion, slight ammoniacal odor		

▼ **SECTION IV: FIRE & EXPLOSIVE HAZARD DATA**

Flash Point:	None	Method Used:	ASTM-D56
Flammable Limits:	N/A	Flame Extension:	N/A
Extinguishing Media:	N/A		
Special Fire Fighting Procedures:	N/A		
Unusual Fire & Explosive Hazards:	N/A		

▼ **SECTION V: HEALTH HAZARD DATA**

Threshold Limit Value:	Not Established	Primary Routes of Entry:	Inhalation, Skin Contact, Eyes & Ingestion.
Effects of Overexposure-Conditions to Avoid:	May cause eye and skin irritation. Inhalation of vapors may cause respiratory irritation, headache and nausea. Harmful if swallowed. Diethylene glycol monoethyl ether may be absorbed through the skin in harmful amounts. Ingestion of diethylene glycol monoethyl ether may cause central nervous system and respiratory depression, gastrointestinal tract, liver and kidney impairment. Avoid contact with eyes and skin. Avoid breathing product vapors or mists. Do not swallow.		
Conditions Aggravated by Use:	Preexisting skin and respiratory disorders.		

**Emergency & First Aid Procedures:**

Eyes:	Immediately flush eyes with water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Wash thoroughly with soap and water.
Ingestion:	Do not induce vomiting. Drink one or two glasses of water to dilute. Get medical attention. Never give anything by mouth to an unconscious person
Inhalation:	Move person to fresh air. If irritation persists; get medical attention.

▼ **SECTION VI: REACTIVITY DATA**

Stability:	Stable	Incompatible Materials:	None known
Hazardous Decomposition Products:	None known	Hazardous Polymerization:	Will Not Occur

▼ **SECTION VII: SPILL OR LEAK PROCEDURES**

Steps to be Taken in Case Material is Released or Spilled:	Small spills, flush with water to sewer system. Dike and contain large spill with inert material and transfer liquid to containers for recovery or disposal.
Waste Disposal Method:	Incineration or approved landfill. Follow Federal, State and Local regulations.

▼ **SECTION VIII: SPECIAL PROTECTION INFORMATION**

Respiratory Protection:	Not normally required. However, is exposure levels are exceeded (see Section II) or if irritation occurs, use of a fully functioning NIOSH approved respirator is recommended.
Ventilation:	Good general ventilation should be sufficient for most conditions. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Impervious gloves
Eye Protection(Specify Type):	Splash goggles
Other Protective Equipment:	None required

▼ **SECTION IX: SPECIAL PRECAUTIONS**

Precautions; Handling & Storing:	Keep from freezing.
Other Precautions:	Keep out of reach of children.

© SCC 06/30/2005  
MILLENNIA BRIGHT DURA GLOSS  
LAMINATE

Name: Ronald T. Cook  
Effective 06/30/2005  
Date:

Title: Manager, Regulatory Affairs  
Supersedes: 11/02/2001

Ref: 29 CFR 1910.1200  
(OSHA)

Changes: Update Section IX

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.